



# BS 980T

## Central Smart SMS and Call Module v2



## Be Informed in Any Situation

In case the sensor parameters in the environment go beyond the threshold values you have determined; it notifies the authorized persons by SMS and call. Since it communicates directly with Sensaway software, it provides management and cost advantages in multiple locations with a single device and sim card.

### GENERAL FEATURES

- Common solution for all locations on the same network
- Notification in case of power cuts thanks to the built-in 6-hour battery / storage battery support
- Sensaway software communication over Ethernet (IP)
- Ability to be managed over the Web
- Send notification in case of sabotage or when Sensaway software is not running
- SMS or Call an unlimited number of users
- LED indicators and LCD screen showing instant situations:



## TECHNICAL SPECIFICATIONS

BS 980T

### DIMENSIONS

Height: 48mm

Width: 140mm

Depth: 100mm

### WEIGHT

220 g.

### ELECTRICITY AND OPERATING REQUIREMENTS

-40°C, +85°C & 0 – 85 %RH Humidity

Power: 12 Volt / 2A

### MODEM FEATURES

Simcom 4G - A7682E

Band: LTE-FDD GSM/GPRS/EDGE 900/1800 MHz

### CONNECTIONS

100Mbps ethernet LAN/WAN

Standard Size Sim Card Slot

### MOUNTING

Wall Mount

Desktop Mount

### BATTERY

Battery Type: Li-Polymer

Capacity: 3.7V 1.800 mAh

### MONITORING & MANAGEMENT SOFTWARE

Sensaway Monitoring & Management Software

### STATUS DISPLAY

320 x 240 px TFT LCD Screen

2 Led Indicators for power status (Green, Yellow)

### ACCESSORIES

Installation Guide

12V DC 2A Adapter

External GSM Antenna

### NETWORK AND SECURITY

10/100 Ethernet

Password Protection, IP Address Filtering